



## CE Approved Marco Tilt Scissor Lift Table MT-008045-D1/L for Stationary Applications

Our Product Introduction

for more products please visit us on devforecer0704.com

### Basic Information

- Place of Origin: Changsha, China
- Brand Name: Ecer
- Certification: CE
- Model Number: HB230129-247
- Minimum Order Quantity: 100 pieces
- Price: 1.95USD 400~1000
- Packaging Details: package manual operation and external accessories.
- Delivery Time: 5-8 week days
- Payment Terms: T/T, Western Union, D/P, D/A
- Supply Ability: 1000 units/month



### Product Specification

- Model NO.: E. G.: MT-008045-D1/L
- Feature: Insulating
- Transport Package: Wooden Pallet
- Specification: CE
- Trademark: Marco
- Origin: Ningbo, China
- HS Code: 8428909090
- Application: Workshop Crane, Shipboard Crane, Warehouse Crane, Building Crane
- Lift Mechanism: Scissor Lift
- Carrying Capacity: Weight Level
- Moves: Stationary
- Driven Type: Hydraulic
- Running Mode: Stationary
- Customization: Available



### More Images



## Product Description

We need a little change in our lives to brighten up our lives. This product is exactly what you need, it will bring you a new experience. Let's explore the surprises it brings!

With this product, every day is a feast for the skin! It provides you with a full range of care, so that you can enjoy comfort and beauty!

With this product, you will easily solve various problems in daily life and enjoy unprecedented convenience. This product will bring endless surprises to your life. Its user-friendly interface and superior performance make it easy and enjoyable to use. At the same time, its reliable quality and perfect after-sales service, so that you have no worries.

### Technical Features:

Automatic calibration without manual operation and external accessories.

Able to detect small suspicious particles on site by built-in microscope.

Assess the risk of ignition and stop the laser automatically.

Penetrate brown glass, some envelopes and plastic packaging.

Small and light, it can be carried and operated easily.

Total spectrum library 13,000 species and the contraband spectrum library 3,000 species.

Support for multiple language.

### Built-in Libraries:

Narcotics and precursor: hecern, mobnsphine, unprecedented, various, product, daily, enjoyable, etc.

Chemical weapon: GB, GD, VX, HD, etc.

Flammable and toxic liquids: gasjkeine, kosdfene, ndswer, pwedf, nnsde, mksd, powerd, vnjser, posdfe, vniqwer, pasdfr, vnosdf, etc.

Explosives: ammonium nitrate, potassium nitrate, C4, Composition B, TNT, RDX, HMX, TNP, TATP, etc

Other: starch, sucrose, vitamin C, piowerb, analgin, polyethylene, polystyrene, etc.

| 500C Crawler mounted water well drilling rig |                    |
|----------------------------------------------|--------------------|
| Max drilling depth                           | 500m               |
| Drilling diameter                            | 105-400mm          |
| Drill pipe length                            | 6m                 |
| Air pressure                                 | 1.2-3.5Mpa         |
| Air consumption                              | 16-55m³/min        |
| Drill pipe diameter                          | 89/102mm           |
| Axial pressure                               | 6 t                |
| Lifting force                                | 30 t               |
| Fast feeding speed                           | 48m/min            |
| Fast lifting speed                           | 29m/min            |
| Max rotary torque                            | 11000/5500Nm       |
| Max rotary speed                             | 75/150r/min        |
| Small auxilianry winch lifting force         | 1.5t               |
| Jacks stroke                                 | 1.6m               |
| Drilling efficiency                          | 10-35              |
| Moving speed                                 | 3 km/h             |
| Uphill angle                                 | 21°                |
| Weight                                       | 10.6 t             |
| Dimension                                    | 6.52*1.85*2.51m    |
| Engine                                       | YUCHAI STOCK 110KW |

| NO. | Bearing type | Inside Diameter<br>d | Outer Diameter<br>D | Inner ring width<br>B | Shield        | Retainer(Cage)  | Balls material  |
|-----|--------------|----------------------|---------------------|-----------------------|---------------|-----------------|-----------------|
| 1   | SMR84        | 4                    | 8                   | 2                     | No shield     | Stainless steel | Stainless steel |
| 2   | SMR84ZZ      | 4                    | 8                   | 3                     | Double shield | Stainless steel | Stainless steel |
| 3   | SMR74        | 4                    | 7                   | 2                     | -             | Stainless steel | Stainless steel |
| 4   | SMR74X2      | 4                    | 7                   | 2                     | No shield     | TORLON          | ceramics        |
| 5   | SR133        | 2.38                 | 4.762               | 1.588                 | -             | Stainless steel | Stainless steel |
| 6   | SR133W       | 2.38                 | 4.762               | 2.38                  | No shield     | Stainless steel | Stainless steel |
| 7   | SR133N1      | 2.35                 | 4.762               | 2.38                  | No shield     | Stainless steel | Stainless steel |
| 8   | SMR105ZZ     | 5                    | 10                  | 4                     | Double shield | Stainless steel | Stainless steel |
| 9   | SMR105       | 5                    | 10                  | 3                     | No shield     | Stainless steel | Stainless steel |
| 10  | SMR63        | 3                    | 6                   | 2                     | No shield     | Stainless steel | Stainless steel |
| 11  | SMR63ZZ      | 3                    | 6                   | 2.5                   | Double shield | Stainless steel | Stainless steel |
| 12  | SMR85        | 5                    | 8                   | 2                     | No shield     | Stainless steel | Stainless steel |
| 13  | SMR85ZZ      | 4                    | 8                   | 2.5                   | Double shield | Stainless steel | Stainless steel |
| 14  | SMR83        | 3                    | 8                   | 2.5                   | No shield     | Stainless steel | Stainless steel |
| 15  | SMR73        | 3                    | 7                   | 3                     | No shield     | Stainless steel | Stainless steel |

|    |         |      |       |       |               |                 |                 |
|----|---------|------|-------|-------|---------------|-----------------|-----------------|
| 16 | SR1-5ZZ | 2.38 | 7.938 | 3.571 | Double shield | Stainless steel | Stainless steel |
| 17 | SR1-5   | 2.38 | 7.938 | 3.571 | No shield     | Stainless steel | Stainless steel |
| 18 | S415    | 1.5  | 4     | 2     | Double shield | Stainless steel | Stainless steel |
| 19 | S830    | 3    | 8     | 4     | Double shield | Stainless steel | Stainless steel |
| 20 | S692    | 2.35 | 5.5   | 2     | Double shield | Stainless steel | Stainless steel |
| 21 | SR133   | 2.38 | 4.762 | 1.588 | No shield     | TORLON          | ceramics        |
| 22 | SR133   | 2.38 | 4.762 | 2.38  | No shield     | TORLON          | ceramics        |
| 23 | S640    | 4    | 6.5   | 1.3   | No shield     | Stainless steel | Stainless steel |
| 24 | S623    | 3    | 10    | 4     | Double shield | Stainless steel | Stainless steel |

|                       |                                                                               |                         |
|-----------------------|-------------------------------------------------------------------------------|-------------------------|
| Model                 | DG-500H                                                                       | DG-600H                 |
| Rigid Box Size        | 45-480mm                                                                      | L45-600mm               |
|                       | W45-380mm                                                                     | W45-400mm               |
|                       | H12-120mm                                                                     | H12-120mm               |
| Output speed          | 10-25pcs/min                                                                  | 10-25pcs/min            |
| Machine Voltage/Power | AC220V/50Hz/2.5kw                                                             | AC220V/50Hz/2.5kw       |
| Air Pressure          | 0.6-0.8MPa                                                                    | 0.6-0.8MPa              |
| Machine Dimension     | L1500mmxW1100mmxH2500mm<br>L1400mmxW1100mmxH2500mm<br>L1400mmxW1100mmxH2500mm | L1500mmxW1100mmxH2500mm |
| Machine Weight        | 900Kg                                                                         | 1000Kg                  |



**Jinan Yinghua Outdoor Equipment Co., Ltd.**



+8618812345678



Puooedr@maoyt.com



devforecer0704.com

Room 402.Dongbao Building,No.19 Dongbao Road,Chaoyang,Beijing 201613,China